

Full-Square Color Monitor/Receivers

TM-2001U



- 20" Diagonal Full Square Dark Tinted Picture Tube
- Hyper Scan High Speed Channel Changer
- New Super Command Universal Remote w/ TV/VCR/Cable Box and DVD control
- Super Command Scrolling OSD
- Return+
- Multi-function Timer with Sleep Timer
- XDS Auto Clock Set
- V-Chip & Channel Guard
- Video & System Features
 - Game Mode
 - Black Level Expansion
 - Apacon
 - English, French, and Spanish Menus
 - Closed Captions w/Text
- Sound Features
 - MTS Stereo with SAP
 - TV Speaker On/Off in Menu
 - Front Firing Speakers
- Inputs/Outputs
 - 2 AV Inputs (1 Front / 1 Rear)
 - 1 Front Headphone Jack
 - 1 Variable Audio Output
 - 1 RF Input
 - 1 BNC Composite Input Loopthrough (adapter included)

	TM-2001U	TM-2701U
Reception format	NTSC, BTSC system (multi-channel sound)	
Reception range	VHF 2 to 13, UHF 14 to 69 Sub mid, mid, super, hyper and ultra bands (181 channel frequency synthesizer system)	
Power source	AC 120 V, 60 Hz	
Power consumption	87 W/1.4 A	113 W/1.8 A
Screen size	20-inch/51 cm measured diagonally full square	27-inch/68 cm measured diagonally full square
Audio output	1 W + 1 W	1.2 W + 1.2 W
Speaker	8 cm round x 1	
Composite video input	BNC x 2 (1 for bridged output), 1.0 Vp-p, 75 ohms, termination switch provided	
Speakers	5 x 9 cm (2" x 3-1/2") oval x 2	
Antenna terminal	75 ohms (VHS/UHF) (F-type connector)	
External input jacks	Video: 1 Vp-p, 75 ohms Audio: 500 mVrms (-4 dBs) high impedance	

TM-2701U



- 27" Diagonal Full Square Dark Tinted Picture Tube
- 2 Line Digital Comb Filter
- 550 Lines Horizontal Resolution
- Hyper Scan High Speed Channel Changer
- New Super Command Universal Remote w/ TV/VCR/Cable Box and DVD control
- Return+
- Multi-function Timer with Sleep Timer
- XDS Auto Clock Set
- V-Chip & Channel Guard
- Video & System Features
 - Black Level Expansion
 - Apacon
 - English, French, and Spanish Menus
 - Closed Captions w/Text
- Sound Features
 - Hyper Surround Sound
 - MTS Stereo with SAP
 - TV Speaker On/Off in Menu
 - Front Firing Speakers
- Inputs/Outputs
 - 1 S-Video Input (Rear)
 - 2 AV Inputs (1 Front / 1 Rear)
 - 1 Variable Audio Output
 - 1 RF Input
 - 1 BNC Composite Input Loopthrough (adapter included)

	TM-2001U	TM-2701U
S-video input jack	-	Y: 1 Vp-p positive, 75 ohms (negative sync provided) C: 0.286 Vp-p (burst signal), 75 ohms
Variable audio output	-	More than 0 to 1550mVrms (+6 dBs) Low impedance (400Hz when modulated 100%)
Headphone jack	Dia. 3.5 mm x 1	-
Dimensions (WHD)	50.3 x 45.2 x 49.3 mm (19-7/8" x 17-7/8" x 19-1/2")	65.4 x 59.3 x 49.4 mm (19-7/8" x 17-7/8" x 19-1/2")
Weight	19.9 kg (43.8 lbs.)	31.1 kg (68.5 lbs.)
Accessories	Remote control unit x 1 AA battery x 2 BNC connector box x 1	